

Hinged & Locking Covers



Hinged and locking access covers offer a number of benefits to both network operators and contractors through a variety of unique features.

The covers are made easier to lift as a result of the hinge mechanism and smaller lid sizes, addressing both Health & Safety as well as operational issues.




The covers are designed to offer either side or front access, however by simply removing the hinged covers, access can be gained all round.

In the open position, covers are blocked at 105 degrees & 90 degrees to avoid any risk of hazard during access.

All products are site tested extensively and undergo road tests to assure they fully comply with the relevant standards and are fit for purpose.



A variety of locking options are available to prevent access and vandalism. Locking devices can be personalised for each operator and all locking devices have been tested for compliance with the NF P20 551.



Padlock Option



Locked at 110 Dea



Turnbuckle option has a choice of security heads.

SIDE ACCESS - SECURE HINGE - DT Series					
EN 124 Loading	Clear Opening	Overall Size	No of Covers	Weight	CSG Reference
D400	750 x 750	910x950x120	2	166Kg	DT4S075075A
D400	1220 x 665	1400x915x150	4	263Kg	DT4S122068AV *
D400	1500 x 750	1600x950x120	4	306Kg	DT4S150075A
D400	1836 x 665	2016x915x150	6	381Kg	DT4S183068AV *
D400	2250 x 750	2415x950x120	6	446Kg	DT4S250075A

FRONT ACCESS - SECURE HINGE - TI Series					
EN 124 Loading	Clear Opening mm	Overall Size mm	No of Covers	Weight	CSG Reference
D400	600 x 450	750x600 x100	2	72Kg	TI4S060045AV
D400	600 x 600	745x772 x100	2	98Kg	TI4S060060AV
D400	800 x 700	945x872 x100	2	130Kg	TI4S080070AV
D400	900 x 600	1100x750 x100	4	132Kg	TI4S090060AV
D400	900 x 900	1084x1100 x100	2	208Kg	TI4S090090AV
D400	1060 x 700	1255x884 x100	4	192Kg	TI4S106070AV
D400	1200 x 600	1400x780 x120	4	208Kg	TI4S120060AV
D400	1200 x 750	1400x930 x120	4	259Kg	TI4S120075AV
D400	1300 x 800	1500x980 x100	4	247Kg	TI4S130080AV

* These covers are locked as standard

TI Series covers are all locked as standard

Castings Services Limited
Head Office & Valve Division
Langley Road South, Salford
Manchester, England. M6 6TZ



Pipeline Sales Office
Unit 7, Oaktree Business Park
Cadley Hill Road, Swadlincote
Derbyshire. DE11 9DJ

Tel : 00 44 (0) 161 745 9095
Fax: 00 44 (0) 161 745 8996

E-Mail: sales@castings-services.co.uk

Tel : 00 44 (0) 1283 554720
Fax: 00 44 (0) 1283 554721

Web: www.castings-services.co.uk

Castings Services reserve the right to make any design modifications without giving prior notice. E & O E.
Document Ref: D400H&Lcovers.01