



Flanged Bellmouth

BS EN 545/598 ISO-2531

Class K12

Nominal Size DN mm	Length L mm	Dia 'D' mm	Mass Kg	CSG Product Reference
80mm	135	150	5.3	F080BEL
100mm	140	175	6.5	F100BEL
150mm	150	230	10.7	F150BEL
200mm	170	290	14.8	F200BEL
250mm	185	345	21.0	F250BEL
300mm	205	405	30.0	F300BEL
350mm	220	460	38.0	F350BEL
400mm	240	520	49.5	F400BEL
450mm	255	575	62.0	F450BEL
500mm	275	635	80.0	F500BEL
600mm	310	750	120.0	F600BEL
700mm	345	865	146.0	F700BEL
800mm	380	980	197.0	F800BEL
900mm	415	1095	250.0	F900BEL
1000mm	450	1210	331.0	FZ10BEL
1100mm	465	1400	435.0	FZ11BEL
1200mm	520	1440	512.0	FZ12BEL
1400mm	590	1670	702.0	FZ14BEL
1600mm	660	1900	995.0	FZ16BEL

Coating Options:

International : Bitumen Coated in/out

UK : Blue Epoxy - EN545 Potable Water

Red Epoxy - EN598 Non Potable Water

Castings Services Limited
Head Office & Valve Division
Langley Road South, Salford
Manchester, England. M6 6TZ

Tel : 00 44 (0) 161 745 9095
Fax: 00 44 (0) 161 745 8996



E-Mail: sales@castings-services.co.uk

Web: www.castings-services.co.uk

Pipeline Sales Office

Unit 7, Oaktree Business Park
Cadley Hill Road, Swadlincote
Derbyshire. DE11 9DJ

Tel : 00 44 (0) 1283 554720
Fax: 00 44 (0) 1283 554721

Castings Services reserve the right to make any design modifications without giving prior notice. E & O E.

Document Ref: FBEL.01