

Wafer Butterfly Valves

BS 5155

Sizes 50 - 300mm

Key Features

- Conforms to BS 5155 & EN 593
- Ductile Iron Body / EPDM Liner.
- Disc in Stainless Steel 316, Nickel Plated DI or Aluminium Bronze.
- Stainless Steel Stem SS416 or 304.
- Operating Pressure 16 Bar Temperature -10 to +120 Deg C.
- Wafer Body to fit between PN10 or PN16 flanges
- ISO Top Flange as standard.
- Lever Operation up to 200mm as standard.
- Gearbox and Handwheel operation on sizes 250-300mm.
- WRAS Approved Epoxy Coating.

Wafer Butterfly Valve



Options:

- * Available with cast iron body.
- * Gearbox/ Handwheel.
- * Open/close indicator and switch.
- * Can be supplied with Actuator.
- * Available with Bevel Gearbox.

Note: Options subject to agreed lead times

Castings Services Limited
Head Office & Valve Division
Langley Road South, Salford
Manchester, England. M6 6TZ

Tel : 00 44 (0) 161 745 9095
Fax: 00 44 (0) 161 745 8996



E-Mail: sales@castings-services.co.uk

Web: www.castings-services.co.uk

Pipeline Sales Office

Unit 7, Oaktree Business Park
Cadley Hill Road, Swadlincote
Derbyshire. DE11 9DJ

Tel : 00 44 (0) 1283 554720
Fax: 00 44 (0) 1283 554721